# SAFETY DATA SHEET

### 1. Identification

1000025928 Marvalosa MicroAire 3000 - Micro Metered Air Freshener 11-04-2015
Nyco Products Company. 5332 Dansher Road Countryside, IL 60525 USA
General Assistance (708) 579-8100
ChemTrec 1-800-424-9300
-
02
11-04-2015
Not available.
None known.

### 2. Hazard(s) identification

Label elements

Physical hazards	Flammable aerosols Category 1		
Health hazards	Serious eye damage/eye irritation	Category 2A	
	Specific target organ toxicity, single exposure	Category 3 narcotic effects	
Environmental hazards	Not classified.		
OSHA defined hazards	Not classified.		



Signal word	Danger		
Hazard statement	Extremely flammable aerosol. Causes serious eye irritation. May cause drowsiness or dizziness.		
Precautionary statement			
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear eye protection/face protection.		
Response	If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention.		
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.		
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.		
Hazard(s) not otherwise classified (HNOC)	None known.		
Supplemental information	None.		

## 3. Composition/information on ingredients

**Mixtures** 

synonyms CAS number	%
67-64-1	40 - 60
	<b>,</b> ,

Chemical name	Common name and synonyms	CAS number	%
Diethylene Glycol Monoethyl Eth	er	111-90-0	10 - 20
Propane		74-98-6	10 - 20
Isobutane		75-28-5	2.5 - 10
Allyl Heptanoate		142-19-8	0.1 - 1
Amyl Salicylate		2050-08-0	0.1 - 1
Benzyl Acetate		140-11-4	0.1 - 1
Diphenyl Oxide		101-84-8	0.1 - 1
Other components below reporta	ble levels		2.5 - 10

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

### 4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.	
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.	
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.	
Ingestion	In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.	
Most important symptoms/effects, acute and delayed	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.	
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.	
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.	

### 5. Fire-fighting measures

Suitable extinguishing media	Alcohol resistant foam. Powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol.

### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Level 2 Aerosol. Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure controls/personal protection

### **Occupational exposure limits**

### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Туре	Value	Form
PEL	2400 mg/m3	
	1000 ppm	
PEL	7 mg/m3	Vapor.
	1 ppm	Vapor.
PEL	1800 mg/m3	
	1000 ppm	
Туре	Value	Form
STEL	500 ppm	
TWA	250 ppm	
TWA	10 ppm	
STEL	2 ppm	Vapor.
TWA	1 ppm	Vapor.
STEL	1000 ppm	
al Hazards		
Туре	Value	Form
TWA	590 mg/m3	
	250 ppm	
TWA	7 mg/m3	Vapor.
	-	
	1 ppm	Vapor.
TWA	1900 mg/m3	
	800 ppm	
TWA	1800 mg/m3	
	1000 ppm	
sure Level (WEEL) Guides		
<b>T</b>	Value	
Туре	value	
TWA	140 mg/m3	
	PEL PEL Type STEL TWA TWA STEL STEL Cal Hazards Type TWA TWA TWA	PEL1000 ppm 7 mg/m3PEL1 ppm 1800 mg/m3 1000 ppmTypeValueSTEL500 ppm 250 ppm 10 ppmSTEL2 ppm 10 ppmSTEL2 ppm 1000 ppmTWA1 ppm 1000 ppmSTEL590 mg/m3 250 ppm 1000 ppmTWA590 mg/m3 250 ppm 1000 ppmTWA1 ppm 1000 ppmTWA1 ppm 1000 ppmTWA1 ppm 1000 ppmTWA1 ppm 1000 ppmTWA1 ppm 1000 ppmTWA1 ppm 1000 mg/m3 800 ppm 1000 ppmTWA1 ppm 1800 mg/m3 1000 ppm

ACGIH Biological Expos Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine	*
* - For sampling details, p	lease see the sourc	e document.		
Appropriate engineering controls	should be ma or other engin	tched to conditions. If ap leering controls to maint is have not been establis	oplicable, use pro ain airborne leve	hour) should be used. Ventilation rates ocess enclosures, local exhaust ventilation, Is below recommended exposure limits. If irborne levels to an acceptable level. Provide
Individual protection measu Eye/face protection	=	nal protective equipme lasses with side shields		
Skin protection Hand protection	Wear appropr supplier.	iate chemical resistant g	gloves. Suitable g	gloves can be recommended by the glove
Other	Wear suitable	Wear suitable protective clothing.		
Respiratory protection		If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.		
Thermal hazards	Wear appropr	Wear appropriate thermal protective clothing, when necessary.		
General hygiene considerations	after handling	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.		

# 9. Physical and chemical properties

Appearance	
Physical state	Gas.
Form	Aerosol.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	-156.0 °F (-104.4 °C) propellant estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	1.4 % estimated
Flammability limit - upper (%)	19.6 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	806 °F (430 °C) estimated
Decomposition temperature	Not available.

Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Specific gravity	0.001 estimated
10. Stability and reactivity	1
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Nitrates. Fluorine. Chlorine.

products		

# 11. Toxicological information

Hazardous decomposition

### Information on likely routes of exposure

Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Causes serious eye irritation.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

No hazardous decomposition products are known.

### Information on toxicological effects

Acute toxicity	Narcotic effects.	
Components	Species	Test Results
Acetone (CAS 67-64-1)		
Acute		
Dermal		
LD50	Guinea pig	> 7426 mg/kg, 24 Hours
		> 9.4 ml/kg, 24 Hours
	Rabbit	> 7426 mg/kg, 24 Hours
		> 9.4 ml/kg, 24 Hours
Inhalation		
LC50	Rat	55700 ppm, 3 Hours
		132 mg/l, 3 Hours
		50.1 mg/l
Oral		ů –
LD50	Rat	5800 mg/kg
		2.2 ml/kg
Allyl Heptanoate (CAS 142-19	-8)	Ĵ
<u>Acute</u>	-,	
Oral		
LD50	Rat	218 mg/kg
Benzyl Acetate (CAS 140-11-4	4)	
Acute		
Dermal		
LD50	Rabbit	> 5 g/kg
Oral		
LD50	Mouse	> 2000 mg/kg

Components	Species	Test Results
	Rat	> 2000 mg/kg
Diethylene Glycol Monoethyl Ethe	er (CAS 111-90-0)	
<u>Acute</u>		
Dermal		
LD50	Guinea pig	5900 mg/kg, Days
	Rabbit	9143 mg/kg, 24 Hours
		8500 mg/kg, 2 Hours
Oral		
LD50	Mouse	6031 mg/kg
	Rat	> 5000 mg/kg
Diphenyl Oxide (CAS 101-84-8)		
<u>Acute</u>		
Oral		
LD50	Rat	> 5000 mg/kg
sobutane (CAS 75-28-5)		
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
Propane (CAS 74-98-6)		
<u>Acute</u>		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
		658 mg/l/4h
* Estimates for product may h	be based on additional component data not sh	nown
Skin corrosion/irritation	Prolonged skin contact may cause tempora	
Serious eye damage/eye rritation	Causes serious eye irritation.	
Respiratory or skin sensitization	n	
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin	sensitization.
Germ cell mutagenicity		y components present at greater than 0.1% are
Carcinogenicity	This product is not considered to be a carc	inogen by IARC, ACGIH, NTP, or OSHA.
IARC Monographs. Overall	Evaluation of Carcinogenicity	
Benzyl Acetate (CAS 140 OSHA Specifically Regulate	D-11-4) 3 Not class ad Substances (29 CFR 1910.1001-1050)	sifiable as to carcinogenicity to humans.
Not listed.		
	ogram (NTP) Report on Carcinogens	
Not available.		
Reproductive toxicity	This product is not expected to cause repro	oductive or developmental effects.
Specific target organ toxicity -	May cause drowsiness and dizziness.	
single exposure		
	Not classified.	

### 12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Components		Species	Test Results
Acetone (CAS 67-64-2	1)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours
Benzyl Acetate (CAS	140-11-4)		
Aquatic			
Fish	LC50	Medaka, high-eyes (Oryzias latipes)	3.48 - 4.6 mg/l, 96 hours
Diethylene Glycol Mor	noethyl Ether (CAS	111-90-0)	
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	> 10000 mg/l, 96 hours
Diphenyl Oxide (CAS	101-84-8)		
Aquatic			
Fish	LC50	Sheepshead minnow (Cyprinodon variegatus)	1.8 - 3.2 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

**Persistence and degradability** No data is available on the degradability of this product.

#### **Bioaccumulative potential**

Partition coefficient n-o	octanol / water (log Kow)	
Acetone		-0.24
Benzyl Acetate		1.96
Diethylene Glycol Monoe	thyl Ether	-0.54
Diphenyl Oxide		4.21
Isobutane		2.76
Propane		2.36
Mobility in soil	No data available.	

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

### 13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

### 14. Transport information

DOT	
UN number	UN1950
UN proper shipping name	Aerosols, flammable, (each not exceeding 1 L capacity)
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1

Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety
	instructions, SDS and emergency procedures before handling.

Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

#### ΙΑΤΑ

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	No.
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.
Packaging Exceptions	LTD QTY
IMDG	
UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	No.
EmS	F-D, S-U
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Packaging Exceptions	LTD QTY
Transport in bulk according to	Not applicable.
Annex II of MARPOL 73/78 and	
the IBC Code	

DOT





### 15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

# TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated. CERCLA Hazardous Substance List (40 CFR 302.4) Acetone (CAS 67-64-1) Listed. SARA 304 Emergency release notification Not regulated. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) Not listed. Superfund Amendments and Reauthorization Act of 1986 (SARA) Immediate Hazard - Yes **Hazard categories** Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No SARA 302 Extremely hazardous substance Not listed. SARA 311/312 Hazardous No chemical SARA 313 (TRI reporting) Not regulated. Other federal regulations Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List Not regulated. Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) Isobutane (CAS 75-28-5) Propane (CAS 74-98-6) Safe Drinking Water Act Not regulated. (SDWA) Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and **Chemical Code Number** Acetone (CAS 67-64-1) 6532 Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c)) 35 %WV Acetone (CAS 67-64-1) **DEA Exempt Chemical Mixtures Code Number** Acetone (CAS 67-64-1) 6532 US state regulations US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100) Not listed. US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Acetone (CAS 67-64-1) Isobutane (CAS 75-28-5)

### US. Massachusetts RTK - Substance List

Acetone (CAS 67-64-1) Diphenyl Oxide (CAS 101-84-8) Isobutane (CAS 75-28-5) Propane (CAS 74-98-6)

#### US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1) Benzyl Acetate (CAS 140-11-4) Diphenyl Oxide (CAS 101-84-8) Isobutane (CAS 75-28-5) Propane (CAS 74-98-6)

#### US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1) Diphenyl Oxide (CAS 101-84-8) Isobutane (CAS 75-28-5) Propane (CAS 74-98-6)

### US. Rhode Island RTK

Acetone (CAS 67-64-1) Isobutane (CAS 75-28-5) Propane (CAS 74-98-6)

#### **US. California Proposition 65**

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

### 16. Other information, including date of preparation or last revision

Issue date	11-04-2015
Revision date	11-04-2015
Version #	02
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.