



# e.COAT

## ZINC-FREE FLOOR FINISH

### DESCRIPTION

**e.COAT** is an environmentally preferable floor finish that is metal free and contains no zinc or other heavy metals. **e.COAT** provides a long lasting high gloss appearance and can be used with most maintenance programs and types of floors.

Non-yellowing film resists penetration of dirt and soil. Meets and exceeds slip resistance standard ASTM D2047.

- High Gloss
- Durable
- Can be maintained with scrub & recoat, spray buffing and high speed burnishing programs

### APPLICATIONS

Schools  
Health Care  
Commercial / Retail  
Super Markets

### FOR USE ON

Resilient Tiles  
Terrazzo  
Synthetic Flooring  
Sealed Wood

### DIRECTIONS

Read entire label before using this product.

Thoroughly strip and remove all old wax and finish from floor using e.Mulsify Low Odor Floor Stripper. Floor must be clean, dry and free of residue before applying finish.

Apply uniform coats of finish with a clean synthetic mop or applicator system. Allow each coat of finish to thoroughly dry before applying additional coats.

**This finish meets or exceeds slip resistance standard ASTM D2047.**

Dispose of this product and waste generated from this product in accordance with all applicable local, state and Federal regulations.

### CHEMICAL & PHYSICAL PROPERTIES

Color / Appearance.....	Off white polymer emulsion
Color of Dried Film.....	Glossy, clear non-yellowing
pH.....	8.0 - 9.0
Non-Volatile Solids.....	20%
Coverage.....	2,000 - 2,500 square feet per gallon
Freeze - Thaw Stability.....	Do not freeze
Recoatability.....	Excellent
Removability.....	Excellent
Slip Resistance.....	Greater than 0.5 coefficient of friction. Meets or exceeds ASTM D2047

MANUFACTURED BY:



Wear protective gloves/protective clothing/eye protection/face protection.  
Utilice guantes protectores y ropa protectora y protección ocular/ facial protección.

GS501