



Defoam

Anti-Foam Additive

Eliminate troublesome foam with this concentrated defoaming agent. Stops foam in return tanks which interferes with the operation of equipment. Controls foam caused by detergents, proteins, and many other causes. Effectively defoams in a variety of high and low pressure applications. Highly concentrated and longer lasting. Saves time and money. Improves efficiency of machine operation, reduces down time and repairs. Nontoxic. Noncorrosive.

DIRECTIONS

Read the entire label and SDS for proper use, handling and storage before using this product.

Return tanks: Add ½ - 1 oz. per gallon of return tank capacity.

Industrial & CIP: Add 1 oz. per 50 gallons of mixing tank capacity.

Surface spraying: Add 1 part Defoam to 10-20 parts of water. Spray directly onto foam.

FAST FACTS

- Defoams
- Highly concentrated
- Use in carpet extraction machines
- Ideal for industrial cleaning

MARKETS

- Building Service Contractors
- Education
- Transportation
- Industry & Manufacturing

SPECIFICATIONS

Color	White
Scent	Pleasant
pH	7.0 - 8.0
Viscosity	Slightly Viscous

PACKAGING

NL640-Q12	12x1 Quarts/Case
NL640-G4	4x1 Gallons/Case
NL640-D55	55 Gallon Drum



Nycoco Products Company

800.752.4754

nycoproducts.com

© NPC FF.NL640.071213

Refer to SDS for more information.