



SAFETY DATA SHEET

Issue Date 16-May-2019

Revision Date 27-Jan-2021

Version 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Product Name Power Floor Scrub Degreaser

Other means of identification

Product Code EZ013-480

Synonyms None

Details of the supplier of the safety data sheet

Company Name Nycoco Products Company
5332 Dansher Road, Countryside, IL 60525
(708) 579-8100
nycoproducts.com

Emergency telephone number

Emergency Telephone Chemtrec 1-800-424-9300

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

| | |
|-----------------------------------|---------------------------|
| Acute toxicity - Oral | Category 5 |
| Acute toxicity - Dermal | Category 5 |
| Skin corrosion/irritation | Category 1 Sub-category B |
| Serious eye damage/eye irritation | Category 1 |

Label elements

Emergency Overview

Danger

Hazard statements

May be harmful if swallowed

Causes severe skin burns and eye damage



Appearance Clear Blue

Physical state Liquid

Odor Mild Sweet Solvent

Precautionary Statements - Prevention

Do not breathe dust/fume/gas/mist/vapors/spray
 Wash face, hands and any exposed skin thoroughly after handling
 Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

Specific Treatment (See Section 4 on the SDS)
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 Immediately call a POISON CENTER or doctor/physician
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 Wash contaminated clothing before reuse
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 Immediately call a POISON CENTER or doctor/physician
 IF SWALLOWED: Rinse mouth. DO NOT induce vomiting
 Drink plenty of water
 Immediately call a POISON CENTER or doctor/physician

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Disposal should be in accordance with applicable regional, national and local laws and regulations

Hazards not otherwise classified (HNOC)**Other Information**

Unknown Acute Toxicity 0.03799% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name | CAS No. | Weight-% | Trade Secret |
|---------------------|-----------|----------|--------------|
| 2-butoxyethanol | 111-76-2 | 5-10 | * |
| Potassium Hydroxide | 1310-58-3 | 1-5 | * |
| Monoethanolamine | 141-43-5 | 1-5 | * |
| Sodium Metasilicate | 6834-92-0 | 1-5 | * |

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures

| | |
|---|---|
| General advice | Immediate medical attention is required. |
| Skin Contact | Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. For minor skin contact, avoid spreading material on unaffected skin. For severe burns, immediate medical attention is required. |
| Eye contact | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. |
| Inhalation | Remove to fresh air. Get medical attention for any breathing difficulty. |
| Ingestion | Rinse mouth. Do NOT induce vomiting. Drink plenty of water. Call a physician or poison control center immediately. |
| Self-protection of the first aider | Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. |

Most important symptoms and effects, both acute and delayed

Symptoms Any additional important symptoms and effects are described in Section 11: Toxicology

Information.

Indication of any immediate medical attention and special treatment needed

Note to physicians

Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure. Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating and toxic gases and vapors. In the event of fire and/or explosion do not breathe fumes.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions

Avoid contact with skin, eyes or clothing. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Use personal protective equipment as required.

Environmental precautions

Environmental precautions

Do not allow into any storm sewer drains, lakes, streams, ponds, estuaries, oceans or other surface water bodies. Should not be released into the environment. Dispose of according to all local city, state and federal rules and regulations.

Methods and material for containment and cleaning up

Methods for containment

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Dike far ahead of liquid spill for later disposal. Soak up with inert absorbent material. Take up mechanically, placing in appropriate containers for disposal. Clean contaminated surface thoroughly. Prevent product from entering drains. Dam up. After cleaning, flush away traces with water.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation, especially in confined areas. In case of insufficient ventilation, wear suitable respiratory equipment. Use only with adequate ventilation and in closed systems.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep out of the reach of children. Keep container tightly closed in a dry and well-ventilated place. Keep in properly labeled containers.

Incompatible materials Strong acids. Aluminum. Incompatible with strong acids and bases. Incompatible with oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

| Chemical Name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|----------------------------------|--|---|---|
| 2-butoxyethanol 111-76-2 | TWA: 20 ppm | TWA: 50 ppm TWA: 240 mg/m ³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m ³ (vacated) S* S* | IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m ³ |
| Potassium Hydroxide 1310-58-3 | Ceiling: 2 mg/m ³ | (vacated) Ceiling: 2 mg/m ³ | Ceiling: 2 mg/m ³ |
| Monoethanolamine 141-43-5 | STEL: 6 ppm TWA: 3 ppm | TWA: 3 ppm TWA: 6 mg/m ³ (vacated) TWA: 3 ppm (vacated) TWA: 8 mg/m ³ (vacated) STEL: 6 ppm (vacated) STEL: 15 mg/m ³ | IDLH: 30 ppm TWA: 3 ppm TWA: 8 mg/m ³ STEL: 6 ppm STEL: 15 mg/m ³ |
| Diethanolamine 111-42-2 | TWA: 1 mg/m ³ inhalable fraction and vapor S* | (vacated) TWA: 3 ppm (vacated) TWA: 15 mg/m ³ | TWA: 3 ppm TWA: 15 mg/m ³ |
| Sodium Hydroxide 1310-73-2 | Ceiling: 2 mg/m ³ | TWA: 2 mg/m ³ (vacated) Ceiling: 2 mg/m ³ | IDLH: 10 mg/m ³ Ceiling: 2 mg/m ³ |

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers, Eyewash stations & Ventilation systems.

Individual protection measures, such as personal protective equipment

- Eye/face protection** Tight sealing safety goggles. Wear a face shield if splashing hazard exists.
- Skin and body protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.
- Respiratory protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

General Hygiene When using do not eat, drink or smoke. Keep away from food, drink and animal feeding stuffs. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Avoid contact with skin, eyes or clothing. Take off all contaminated clothing and wash it before reuse. Wear suitable gloves and eye/face protection.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

| | |
|-----------------------|--------------------------|
| Physical state | Liquid |
| Appearance | Clear Blue |
| Color | Blue |
| Odor | Mild Sweet Solvent |
| Odor threshold | No Information available |

| <u>Property</u> | <u>Values</u> | <u>Remarks • Method</u> |
|-------------------------------|--------------------------|-------------------------|
| pH | 13.0 - 14.0 | |
| Specific Gravity | 1.065 | |
| Viscosity | < 25 cP @ 25°C | |
| Melting point/freezing point | No Information available | |
| Flash point | > 140 °F | |
| Boiling point / boiling range | 100 °C / 212 °F Degrees | |
| Evaporation rate | No Information available | |
| Flammability (solid, gas) | No data available | |
| Flammability Limits in Air | | |
| Upper flammability limit: | No Information available | |
| Lower flammability limit: | No Information available | |
| Vapor pressure | No Information available | |
| Vapor density | No Information available | |
| Water solubility | Complete | |
| Partition coefficient | No Information available | |
| Autoignition temperature | No Information available | |
| Decomposition temperature | No Information available | |

Other Information

| | |
|-----------------|------|
| Density Lbs/Gal | 8.87 |
| VOC Content (%) | 10 |

10. STABILITY AND REACTIVITY**Reactivity**

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Exposure to air or moisture over prolonged periods.

Incompatible materials

Strong acids. Aluminum. Incompatible with strong acids and bases. Incompatible with oxidizing agents.

Hazardous Decomposition Products

Thermal decomposition can lead to release of irritating and toxic gases and vapors.

11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

| | |
|----------------------------|---|
| Product Information | The primary effects and toxicity of this material are due to its corrosive nature. |
| Inhalation | Avoid breathing vapors or mists. Breathing of vapor can cause respiratory irritation and inflammation. Breathing of mist or liquid can cause burns to the respiratory tract. |
| Eye contact | Avoid contact with eyes. Corrosive. Causes severe eye damage. |
| Skin Contact | May be harmful in contact with skin. Avoid contact with skin. Corrosive. Contact with skin may cause severe irritation and burns. Maybe harmful if absorbed through skin. |
| Ingestion | May be harmful if swallowed. Ingestion causes acute irritation and burns to the mucous membranes of the mouth, trachea, esophagus and stomach. Ingestion may result in the absorption of potentially harmful amounts leading to possible liver and kidney damage. |

| Chemical Name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|----------------------------------|----------------------|-------------------------|--|
| 2-butoxyethanol 111-76-2 | = 470 mg/kg (Rat) | = 435 mg/kg (Rabbit) | = 450 ppm (Rat) 4 h = 486 ppm (Rat) 4 h |
| Potassium Hydroxide 1310-58-3 | = 284 mg/kg (Rat) | - | - |
| Monoethanolamine 141-43-5 | = 1720 mg/kg (Rat) | = 1000 mg/kg (Rabbit) | - |
| Sodium Metasilicate 6834-92-0 | = 1153 mg/kg (Rat) | - | - |

Information on toxicological effects

Symptoms No Information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Corrosivity Causes burns. Extremely corrosive and destructive to tissue. Risk of serious damage to eyes.

Sensitization No Information available.

Germ cell mutagenicity No Information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

| Chemical Name | ACGIH | IARC | NTP | OSHA |
|-----------------------------|-------|---------|-----|------|
| 2-butoxyethanol 111-76-2 | A3 | Group 3 | - | - |

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - *Animal Carcinogen*

IARC (International Agency for Research on Cancer)

Group 3 - *Not classifiable as a human carcinogen*

Reproductive toxicity No Information available.

STOT - single exposure No Information available.

STOT - repeated exposure No Information available.

Chronic toxicity Chronic exposure to corrosive fumes/gases may cause erosion of the teeth followed by jaw necrosis. Bronchial irritation with chronic cough and frequent attacks of pneumonia are common. Gastrointestinal disturbances may also be seen. Avoid repeated exposure. Possible risk of irreversible effects. May cause adverse effects on the bone marrow and blood-forming system. May cause adverse liver effects.

Target organ effects Blood, Central nervous system, EYES, hematopoietic system, Kidney, Liver, Respiratory system, Skin.

Aspiration hazard No Information available.

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity 0.03799% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 3,707.00

ATEmix (dermal) 4,950.50

ATEmix (inhalation-dust/mist) 15.00

12. ECOLOGICAL INFORMATION**Ecotoxicity**

0.03799% of the mixture consists of components(s) of unknown hazards to the aquatic environment

| Chemical Name | Algae/aquatic plants | Fish | Crustacea |
|------------------------------|---|--|---------------------------------------|
| 2-butoxyethanol 111-76-2 | - | 1490: 96 h Lepomis macrochirus mg/L LC50 static 2950: 96 h Lepomis macrochirus mg/L LC50 | 1000: 48 h Daphnia magna mg/L EC50 |
| Monoethanolamine 141-43-5 | 15: 72 h Desmodesmus subspicatus mg/L EC50 | 114 - 196: 96 h Oncorhynchus mykiss mg/L LC50 static 300 - 1000: 96 h Lepomis macrochirus mg/L LC50 static 227: 96 h Pimephales promelas mg/L LC50 flow-through | 65: 48 h Daphnia magna mg/L EC50 |

| | | | |
|--|--|--|--|
| | | 3684: 96 h Brachydanio rerio mg/L LC50 static 200: 96 h Oncorhynchus mykiss mg/L LC50 flow-through | |
| Sodium Metasilicate 6834-92-0 | - | 210: 96 h Brachydanio rerio mg/L LC50 210: 96 h Brachydanio rerio mg/L LC50 semi-static | - |
| Tetrasodium EDTA 64-02-8 | 1.01: 72 h Desmodesmus subspicatus mg/L EC50 | 41: 96 h Lepomis macrochirus mg/L LC50 static 59.8: 96 h Pimephales promelas mg/L LC50 static | - |
| Sodium Sulfate 7757-82-6 | - | 13500 - 14500: 96 h Pimephales promelas mg/L LC50 3040 - 4380: 96 h Lepomis macrochirus mg/L LC50 static 13500: 96 h Lepomis macrochirus mg/L LC50 6800: 96 h Pimephales promelas mg/L LC50 static | 2564: 48 h Daphnia magna mg/L EC50 |
| Diethanolamine 111-42-2 | 2.1 - 2.3: 96 h Pseudokirchneriella subcapitata mg/L EC50 7.8: 72 h Desmodesmus subspicatus mg/L EC50 | 1200 - 1580: 96 h Pimephales promelas mg/L LC50 static 4460 - 4980: 96 h Pimephales promelas mg/L LC50 flow-through 600 - 1000: 96 h Lepomis macrochirus mg/L LC50 static | 55: 48 h Daphnia magna mg/L EC50 |
| Trisodium nitrilotriacetate 5064-31-3 | - | 175 - 225: 96 h Lepomis macrochirus mg/L LC50 static 560 - 1000: 96 h Oryzias latipes mg/L LC50 560 - 1000: 96 h Oryzias latipes mg/L LC50 semi-static 560 - 1000: 96 h Poecilia reticulata mg/L LC50 560 - 1000: 96 h Poecilia reticulata mg/L LC50 semi-static 72 - 133: 96 h Oncorhynchus mykiss mg/L LC50 static 93 - 170: 96 h Pimephales promelas mg/L LC50 flow-through 114: 96 h Pimephales promelas mg/L LC50 252: 96 h Lepomis macrochirus mg/L LC50 470: 96 h Pimephales promelas mg/L LC50 static | 560 - 1000: 48 h Daphnia magna mg/L LC50 |
| Sodium Hydroxide 1310-73-2 | - | 45.4: 96 h Oncorhynchus mykiss mg/L LC50 static | - |

Persistence and degradability

No Information available.

Bioaccumulation

Bioaccumulative potential.

| Chemical Name | Partition coefficient |
|----------------------------------|-----------------------|
| 2-butoxyethanol 111-76-2 | 0.81 |
| Potassium Hydroxide 1310-58-3 | 0.65 0.83 |
| Monoethanolamine 141-43-5 | -1.91 |

Other adverse effects

No Information available

13. DISPOSAL CONSIDERATIONS**Waste treatment methods**

| | |
|-------------------------------|---|
| Disposal of wastes | Disposal should be in accordance with applicable regional, national and local laws and regulations. |
| Contaminated packaging | Do not reuse container. |

This product contains one or more substances that are listed with the State of California as a hazardous waste.

| Chemical Name | California Hazardous Waste Status |
|----------------------------------|-----------------------------------|
| Potassium Hydroxide 1310-58-3 | Toxic Corrosive |

14. TRANSPORT INFORMATION

Per CFR 173.154 (b)(2), for corrosive materials in Packaging Group III, this product can ship as Limited Quantity if packaged not over 5.0 L (1.3 gallon) net capacity each for liquids or not over 5.0 kg (11 lbs) net capacity each for solids, packed in a strong outer packaging. Must not exceed 30 kg (66 pounds) gross weight.

DOT

| | |
|--|--|
| UN/ID No. | UN1760 |
| Proper shipping name | Corrosive liquids, n.o.s. |
| Hazard Class | 8 |
| Packing Group | III |
| Special Provisions | IB3, T7, TP1, TP28 |
| Description | UN1760, Corrosive liquids, n.o.s (contains Potassium Hydroxide and Ethanolamine), 8, III |
| Emergency Response Guide Number | 154 |

TDG

| | |
|-----------------------------|---|
| UN/ID No. | UN1760 |
| Proper shipping name | Corrosive liquids, n.o.s. |
| Hazard Class | 8 |
| Packing Group | III |
| Description | UN1760, Corrosive liquids, n.o.s. (contains Potassium Hydroxide and Ethanolamine), 8. III |

15. REGULATORY INFORMATION

International Inventories

| | |
|-----------------|----------|
| TSCA | Complies |
| DSL/NDSL | Complies |

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

| Chemical Name | SARA 313 - Threshold Values % |
|----------------------------|-------------------------------|
| 2-butoxyethanol - 111-76-2 | 1.0 |

SARA 311/312 Hazard Categories

| | |
|--|-----|
| Acute health hazard | Yes |
| Chronic Health Hazard | Yes |
| Fire hazard | No |
| Sudden release of pressure hazard | No |
| Reactive Hazard | No |

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21

and 40 CFR 122.42)

| Chemical Name | CWA - Reportable Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants | CWA - Hazardous Substances |
|----------------------------------|-----------------------------|------------------------|---------------------------|----------------------------|
| Potassium Hydroxide 1310-58-3 | 1000 lb | - | - | X |

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

| Chemical Name | Hazardous Substances RQs | CERCLA/SARA RQ | Reportable Quantity (RQ) |
|----------------------------------|--------------------------|----------------|---|
| Potassium Hydroxide 1310-58-3 | 1000 lb | - | RQ 1000 lb final RQ RQ 454 kg final RQ |

US State Regulations**California Proposition 65**

WARNING: This product can expose you to chemicals including Diethanolamine, which is known to the state of California to cause cancer. For More Information go to www.P65Warnings.ca.gov.

U.S. State Right-to-Know Regulations

| Chemical Name | New Jersey | Massachusetts | Pennsylvania |
|--|------------|---------------|--------------|
| 2-butoxyethanol 111-76-2 | X | X | X |
| Potassium Hydroxide 1310-58-3 | X | X | X |
| Monoethanolamine 141-43-5 | X | X | X |
| Sodium Sulfate 7757-82-6 | - | X | X |
| Diethanolamine 111-42-2 | X | X | X |
| Trisodium nitrilotriacetate 5064-31-3 | - | X | - |
| Sodium Hydroxide 1310-73-2 | X | X | X |

U.S. EPA Label Information

EPA Pesticide Registration Number Not Applicable

16. OTHER INFORMATION

| | | | | |
|-------------|------------------|----------------|--------------------|---|
| NFPA | Health hazards 3 | Flammability 0 | Instability 0 | Physical and Chemical Properties - Personal protection C |
| HMIS | Health hazards 3 | Flammability 0 | Physical hazards 0 | |

Issue Date 16-May-2019

Revision Date 27-Jan-2021

Revision Note

No Information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet