



# SAFETY DATA SHEET

Issue Date 25-Oct-2021

Revision Date 25-Oct-2021

Version 2

## 1. PRODUCT AND COMPANY IDENTIFICATION

### Product identifier

**Product Name** Low Odor Wax Remover

### Other means of identification

**Product Code** NL90456

**Synonyms** None

### Details of the supplier of the safety data sheet

**Company Name** Nyco Products Company  
5332 Dansher Road,  
Countryside, IL 60525  
(708) 579-8100  
nycoproducts.com

### Emergency telephone number

**Emergency Telephone** Chemtrec 1-800-424-9300

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 1 Sub-category B
Serious eye damage/eye irritation	Category 1

### Label elements

#### Emergency Overview

# Danger

#### **Hazard statements**

Causes severe skin burns and eye damage

May cause respiratory irritation

May cause drowsiness or dizziness



**Appearance** Clear Yellow

**Physical state** Liquid

**Odor** Nil

**Precautionary Statements - Prevention**

Use in a well-ventilated area  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Wear protective gloves/protective clothing/eye protection/face protection  
 Wash face, hands and any exposed skin thoroughly after handling

**Precautionary Statements - Response**

Specific Treatment (See Section 4 on the SDS)  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 Immediately call a POISON CENTER or doctor/physician  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 Wash contaminated clothing before reuse  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 Immediately call a POISON CENTER or doctor/physician  
 IF SWALLOWED: Rinse mouth. DO NOT induce vomiting  
 Drink plenty of water  
 Immediately call a POISON CENTER or doctor/physician

**Precautionary Statements - Storage**

Store locked up

**Precautionary Statements - Disposal**

Disposal should be in accordance with applicable regional, national and local laws and regulations

**Hazards not otherwise classified (HNOC)****Other Information**

- Harmful to aquatic life with long lasting effects
- Harmful to aquatic life

Unknown Acute Toxicity

0.0422% of the mixture consists of ingredient(s) of unknown toxicity

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%	Trade Secret
Monoethanolamine	141-43-5	5-10	*
Potassium Hydroxide	1310-58-3	1-5	*
2-(2-methoxypropoxy)propano	34590-94-8	1-5	*
Diethanolamine	111-42-2	<0.1	*

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

**First aid measures**

<b>General advice</b>	Immediate medical attention is required.
<b>Skin Contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. For minor skin contact, avoid spreading material on unaffected skin. For severe burns, immediate medical attention is required.
<b>Eye contact</b>	Do not rub affected area. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing.
<b>Inhalation</b>	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician or poison control center immediately.
<b>Ingestion</b>	Rinse mouth. Drink plenty of water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.
<b>Self-protection of the first aider</b>	Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

**Most important symptoms and effects, both acute and delayed**

**Symptoms** Any additional important symptoms and effects are described in Section 11: Toxicology Information.

**Indication of any immediate medical attention and special treatment needed**

**Note to physicians** Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure. Treat symptomatically.

**5. FIRE-FIGHTING MEASURES****Suitable extinguishing media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable extinguishing media** Caution: Use of water spray when fighting fire may be inefficient.

**Specific hazards arising from the chemical**

The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating and toxic gases and vapors. In the event of fire and/or explosion do not breathe fumes.

**Explosion data**

**Sensitivity to Mechanical Impact** None.

**Sensitivity to Static Discharge** None.

**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**6. ACCIDENTAL RELEASE MEASURES****Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Avoid contact with skin, eyes or clothing. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Use personal protective equipment as required.

**Environmental precautions**

**Environmental precautions** Do not allow into any storm sewer drains, lakes, streams, ponds, estuaries, oceans or other surface water bodies. Should not be released into the environment. Dispose of according to all local city, state and federal rules and regulations.

**Methods and material for containment and cleaning up**

**Methods for containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Dam up. Dike far ahead of liquid spill for later disposal. Prevent product from entering drains. Soak up with inert absorbent material. Take up mechanically, placing in appropriate containers for disposal. Clean contaminated surface thoroughly. After cleaning, flush away traces with water.

**7. HANDLING AND STORAGE****Precautions for safe handling**

**Advice on safe handling** Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation, especially in confined areas. In case of insufficient ventilation, wear suitable respiratory equipment. Use only with adequate ventilation and in closed systems.

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions** Keep out of the reach of children. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep in properly labeled containers.

**Incompatible materials** Strong acids. Aluminum. Incompatible with strong acids and bases. Incompatible with oxidizing agents.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Control parameters**

**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Monoethanolamine 141-43-5	STEL: 6 ppm TWA: 3 ppm	TWA: 3 ppm TWA: 6 mg/m <sup>3</sup> (vacated) TWA: 3 ppm (vacated) TWA: 8 mg/m <sup>3</sup> (vacated) STEL: 6 ppm (vacated) STEL: 15 mg/m <sup>3</sup>	IDLH: 30 ppm TWA: 3 ppm TWA: 8 mg/m <sup>3</sup> STEL: 6 ppm STEL: 15 mg/m <sup>3</sup>
Potassium Hydroxide 1310-58-3	Ceiling: 2 mg/m <sup>3</sup>	(vacated) Ceiling: 2 mg/m <sup>3</sup>	Ceiling: 2 mg/m <sup>3</sup>
2-(2-methoxypropoxy)propano 34590-94-8	STEL: 150 ppm TWA: 100 ppm S*	TWA: 100 ppm TWA: 600 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 600 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 900 mg/m <sup>3</sup> (vacated) S* S*	IDLH: 600 ppm TWA: 100 ppm TWA: 600 mg/m <sup>3</sup> STEL: 150 ppm STEL: 900 mg/m <sup>3</sup>
Ethanol 64-17-5	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m <sup>3</sup> (vacated) TWA: 1000 ppm (vacated) TWA: 1900 mg/m <sup>3</sup>	IDLH: 3300 ppm TWA: 1000 ppm TWA: 1900 mg/m <sup>3</sup>
Diethanolamine 111-42-2	TWA: 1 mg/m <sup>3</sup> inhalable fraction and vapor S*	(vacated) TWA: 3 ppm (vacated) TWA: 15 mg/m <sup>3</sup>	TWA: 3 ppm TWA: 15 mg/m <sup>3</sup>
Sodium Hydroxide 1310-73-2	Ceiling: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup> (vacated) Ceiling: 2 mg/m <sup>3</sup>	IDLH: 10 mg/m <sup>3</sup> Ceiling: 2 mg/m <sup>3</sup>

NIOSH IDLH *Immediately Dangerous to Life or Health*

**Other Information** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

**Appropriate engineering controls**

**Engineering Controls** Showers, Eyewash stations & Ventilation systems.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** Tight sealing safety goggles. Wear a face shield if splashing hazard exists.

**Skin and body protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

**General Hygiene** Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Avoid contact with skin, eyes or clothing. Take off all contaminated clothing and wash it before reuse. Wear suitable gloves and eye/face protection.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical state</b>	Liquid
<b>Appearance</b>	Clear Yellow
<b>Color</b>	Yellow
<b>Odor</b>	Nil
<b>Odor threshold</b>	No Information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	> 13	
Specific Gravity	1.03	
Viscosity	<25 cP @ 25°C	
Melting point/freezing point	No Information available	
Flash point	No Information available	
Boiling point / boiling range	100 °C / 212 °F Degrees	
Evaporation rate	No Information available	
Flammability (solid, gas)	No data available	
Flammability Limits in Air		
Upper flammability limit:	No Information available	
Lower flammability limit:	No Information available	
Vapor pressure	No Information available	
Vapor density	No Information available	
Water solubility	Complete	
Partition coefficient	No Information available	
Autoignition temperature	No Information available	
Decomposition temperature	No Information available	

### Other Information

Density Lbs/Gal	8.58
VOC Content (%)	11.15

## 10. STABILITY AND REACTIVITY

### Reactivity

No data available

### Chemical stability

Stable under recommended storage conditions.

### Possibility of Hazardous Reactions

None under normal processing.

### Conditions to avoid

Exposure to air or moisture over prolonged periods.

### Incompatible materials

Strong acids. Aluminum. Incompatible with strong acids and bases. Incompatible with oxidizing agents.

### Hazardous Decomposition Products

Thermal decomposition can lead to release of irritating and toxic gases and vapors.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

#### **Product Information**

The primary effects and toxicity of this material are due to its corrosive nature.

#### **Inhalation**

Avoid breathing vapors or mists. Breathing of vapor can cause respiratory irritation and inflammation. Breathing of mist or liquid can cause burns to the respiratory tract. May cause

drowsiness or dizziness.

- Eye contact** Avoid contact with eyes. Corrosive. Causes severe eye damage.
- Skin Contact** Avoid contact with skin. Corrosive. Contact with skin may cause severe irritation and burns.
- Ingestion** Ingestion causes acute irritation and burns to the mucous membranes of the mouth, trachea, esophagus and stomach.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Monoethanolamine 141-43-5	= 1720 mg/kg ( Rat )	= 1000 mg/kg ( Rabbit )	-
Potassium Hydroxide 1310-58-3	= 284 mg/kg ( Rat )	-	-
2-(2-methoxypropoxy)propano 34590-94-8	= 5.35 g/kg ( Rat )	= 9500 mg/kg ( Rabbit )	-
Diethanolamine 111-42-2	= 780 mg/kg ( Rat )	= 11.9 mL/kg ( Rabbit )	-

**Information on toxicological effects**

**Symptoms** No Information available.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

- Corrosivity** Causes burns. Extremely corrosive and destructive to tissue. Risk of serious damage to eyes.
- Sensitization** No Information available.
- Germ cell mutagenicity** No Information available.
- Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen. Ethanol has been shown to be carcinogenic in long-term studies only when consumed as alcoholic beverage.

Chemical Name	ACGIH	IARC	NTP	OSHA
Diethanolamine 111-42-2	A3	Group 2B	-	X

ACGIH (American Conference of Governmental Industrial Hygienists)  
 A3 - *Animal Carcinogen*  
 IARC (International Agency for Research on Cancer)  
 Group 1 - *Carcinogenic to Humans*  
 NTP (National Toxicology Program)  
 Known - *Known Carcinogen*  
 OSHA (Occupational Safety and Health Administration of the US Department of Labor)  
 X - *Present*

- Reproductive toxicity** No Information available.
- STOT - single exposure** No Information available.
- STOT - repeated exposure** No Information available.
- Chronic toxicity** Chronic exposure to corrosive fumes/gases may cause erosion of the teeth followed by jaw necrosis. Bronchial irritation with chronic cough and frequent attacks of pneumonia are common. Gastrointestinal disturbances may also be seen. Ethanol has been shown to be a reproductive toxin only when consumed as an alcoholic beverage. Ethanol has been shown to be carcinogenic in long-term studies only when consumed as alcoholic beverage. Avoid repeated exposure. Possible risk of irreversible effects.
- Target organ effects** Central nervous system, EYES, Respiratory system, Skin.
- Aspiration hazard** No Information available.

**Numerical measures of toxicity - Product Information**

**Unknown Acute Toxicity** 0.0422% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

- ATEmix (oral)** 8,417.30
- ATEmix (dermal)** 11,974.00
- ATEmix (inhalation-dust/mist)** 16.80

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

0.0422% of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Monoethanolamine 141-43-5	15: 72 h <i>Desmodesmus subspicatus</i> mg/L EC50	114 - 196: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 static 300 - 1000: 96 h <i>Lepomis macrochirus</i> mg/L LC50 static 227: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through 3684: 96 h <i>Brachydanio rerio</i> mg/L LC50 static 200: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 flow-through	65: 48 h <i>Daphnia magna</i> mg/L EC50
2-(2-methoxypropoxy)propano 34590-94-8	-	10000: 96 h <i>Pimephales promelas</i> mg/L LC50 static	1919: 48 h <i>Daphnia magna</i> mg/L LC50
Tetrasodium EDTA 64-02-8	1.01: 72 h <i>Desmodesmus subspicatus</i> mg/L EC50	41: 96 h <i>Lepomis macrochirus</i> mg/L LC50 static 59.8: 96 h <i>Pimephales promelas</i> mg/L LC50 static	-
Didecyl Dimethyl Ammonium Chloride 7173-51-5	-	0.97: 96 h <i>Danio rerio</i> mg/L LC50 semi-static	-
Quaternary Ammonium Compounds Benzyl-C12-C16-alkyldimethyl, Chlorides 68424-85-1	-	0.223 - 0.46: 96 h <i>Lepomis macrochirus</i> mg/L LC50 static 0.823 - 1.61: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 static 1.3: 96 h <i>Poecilia reticulata</i> mg/L LC50 semi-static 2.4: 96 h <i>Oryzias latipes</i> mg/L LC50 semi-static	-
Ethanol 64-17-5	-	12.0 - 16.0: 96 h <i>Oncorhynchus mykiss</i> mL/L LC50 static 13400 - 15100: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through 100: 96 h <i>Pimephales promelas</i> mg/L LC50 static	9268 - 14221: 48 h <i>Daphnia magna</i> mg/L LC50 2: 48 h <i>Daphnia magna</i> mg/L EC50 Static
Diethanolamine 111-42-2	2.1 - 2.3: 96 h <i>Pseudokirchneriella subcapitata</i> mg/L EC50 7.8: 72 h <i>Desmodesmus subspicatus</i> mg/L EC50	1200 - 1580: 96 h <i>Pimephales promelas</i> mg/L LC50 static 4460 - 4980: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through 600 - 1000: 96 h <i>Lepomis macrochirus</i> mg/L LC50 static	55: 48 h <i>Daphnia magna</i> mg/L EC50
Trisodium nitrilotriacetate 5064-31-3	-	175 - 225: 96 h <i>Lepomis macrochirus</i> mg/L LC50 static 560 - 1000: 96 h <i>Oryzias latipes</i> mg/L LC50 560 - 1000: 96 h <i>Oryzias latipes</i> mg/L LC50 semi-static 560 - 1000: 96 h <i>Poecilia reticulata</i> mg/L LC50 560 - 1000: 96 h <i>Poecilia reticulata</i> mg/L LC50 semi-static 72 - 133: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 static 93 - 170: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through 114: 96 h <i>Pimephales promelas</i> mg/L LC50 252: 96 h <i>Lepomis macrochirus</i> mg/L LC50 470: 96 h <i>Pimephales promelas</i> mg/L LC50 static	560 - 1000: 48 h <i>Daphnia magna</i> mg/L LC50
Sodium Hydroxide 1310-73-2	-	45.4: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 static	-

**Persistence and degradability**

No Information available.

**Bioaccumulation**

Bioaccumulative potential.

Chemical Name	Partition coefficient
Monoethanolamine 141-43-5	-1.91
Potassium Hydroxide 1310-58-3	0.83
2-(2-methoxypropoxy)propano 34590-94-8	-0.064
Diethanolamine 111-42-2	-2.18

**Other adverse effects** No Information available

### 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

**Disposal of wastes** Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Contaminated packaging** Do not reuse container.

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
Potassium Hydroxide 1310-58-3	Toxic Corrosive

### 14. TRANSPORT INFORMATION

Per CFR 173.154 (b)(2), for corrosive materials in Packaging Group III, this product can ship as Limited Quantity if packaged not over 5.0 L (1.3 gallon) net capacity each for liquids or not over 5.0 kg (11 lbs) net capacity each for solids, packed in a strong outer packaging. Must not exceed 30 kg (66 pounds) gross weight.

#### DOT

**UN/ID No.** UN1760  
**Proper shipping name** Corrosive liquids, n.o.s.  
**Hazard Class** 8  
**Packing Group** III  
**Special Provisions** IB3, T7, TP1, TP28  
**Description** UN1760, Corrosive liquids, n.o.s (contains Potassium Hydroxide and Ethanolamine), 8, III  
**Emergency Response Guide Number** 154

#### TDG

**UN/ID No.** UN1760  
**Proper shipping name** Corrosive liquids, n.o.s.  
**Hazard Class** 8  
**Packing Group** III  
**Description** UN1760, Corrosive liquids, n.o.s. (contains Potassium Hydroxide and Ethanolamine), 8, III

### 15. REGULATORY INFORMATION

#### International Inventories

**TSCA** Complies  
**DSL/NDSL** Complies

#### Legend:

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List



**US Federal Regulations**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
2-(2-methoxypropoxy)propano - 34590-94-8	1.0

**SARA 311/312 Hazard Categories**

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Potassium Hydroxide 1310-58-3	1000 lb	-	-	X

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Potassium Hydroxide 1310-58-3	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ
Diethanolamine 111-42-2	100 lb	-	RQ 100 lb final RQ RQ 45.4 kg final RQ

**US State Regulations**

**California Proposition 65**

WARNING: This product can expose you to chemicals including Diethanolamine, which is known to the state of California to cause cancer. For More Information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Monoethanolamine 141-43-5	X	X	X
Potassium Hydroxide 1310-58-3	X	X	X
2-(2-methoxypropoxy)propano 34590-94-8	X	X	X
Ethanol 64-17-5	X	X	X
Diethanolamine 111-42-2	X	X	X
Trisodium nitrilotriacetate 5064-31-3	-	X	-
Sodium Hydroxide 1310-73-2	X	X	X

**U.S. EPA Label Information**

EPA Pesticide Registration Number Not Applicable

**16. OTHER INFORMATION**

<b>NFPA</b>	Health hazards 3	Flammability 0	Instability 0	Physical and Chemical Properties - Personal protection C
<b>HMIS</b>	Health hazards 3	Flammability 0	Physical hazards 0	

**Issue Date** 25-Oct-2021

**Revision Date** 25-Oct-2021

**Revision Note**  
No Information available

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**